

PRODUCT-DETAILS

CPS25G-50-CV0

BRAIDED SLEEVE CONF CV0 GREY



General Information

Extended Product Type	CPS25G-50-CV0
Product ID	7TCG054800R0046
EAN	5415022131024
Catalog Description	BRAIDED SLEEVE CONF CV0 GREY
Long Description	Flame Retardant Braided Sleeve, Gray Polyester for Temperatures -50 Degrees Celsius (-58 F) up to 150 Celsius (302 F), Nominal Diameter 25mm (0.984 Inches), Expandable Diameter Range 22mm (0.866 Inches) to 30mm (1.18 Inches), Mini-Reel Length 50m (164.04 Feet)

Ordering

EAN	5415022131024
-----	---------------

Dimensions

Product Net Depth / Length	164.04 ft 50 m
Product Net Weight	2.21 lb 1.002 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	7.67 in

	195 mm
Package Level 1 Height	6.29 in
	160 mm
Package Level 1 Depth / Length	7.67 in
	195 mm
Package Level 2 Units	5 piece
Package Level 2 Width	14.76 in
	375 mm
Package Level 2 Height	13.78 in
	350 mm
Package Level 2 Depth / Length	29.53 in
	750 mm

Additional Information

Brand / Label	Catamount
Bundle Diameter	0.04 to 2.6 in 1 to 66 mm
Color	Gray
Material	Polyester
Number of Batteries	0
Product Name	PLASTIC CONDUIT
Product Type	Braided Sleeve
Temperature Range	-58 to 302 °F -50 to 150 °C
UPC	786209146762

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	CPS25G-50-CV0
Instructions and Manuals	CPS25G-50-CV0

Classifications

ETIM 6	EC001937 - Cable protection for installation duct
ETIM 7	EC001937 - Cable protection for installation duct
UNSPSC	39131602
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5392 >> Expandable braided sleeving

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

