

PRODUCT-DETAILS

CPS3G-100-CV0

BR. SLEEVE CONF CV0 GREY



General Information

Extended Product Type	CPS3G-100-CV0
Product ID	7TCG054800R0108
EAN	5415022238181
Catalog Description	BR. SLEEVE CONF CV0 GREY
Long Description	Flame Retardant Braided Sleeve, Gray Polyester for Temperatures -50 Degrees Celsius (-58 F) up to 150 Celsius (302 F), Nominal Diameter 3mm (0.118 Inches), Expandable Diameter Range 2mm (0.079 Inches) to 5mm (0.197 Inches), Mini-Reel Length 100m (328.08 Feet)

Ordering

EAN	5415022238181
-----	---------------

Dimensions

Product Net Depth / Length	328.08 ft 100 m
Product Net Weight	.087 lb 39.456 g

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	14.76 in

	375 mm
Package Level 1 Height	2.56 in 65 mm
Package Level 1 Depth / Length	14.76 in 375 mm
Package Level 2 Units	5 piece
Package Level 2 Width	14.76 in 375 mm
Package Level 2 Height	14.57 in 370 mm
Package Level 2 Depth / Length	14.76 in 375 mm

Additional Information

Brand / Label	Catamount
Bundle Diameter	0.04 to 2.6 in 1 to 66 mm
Color	Gray
Material	Polyester
Number of Batteries	0
Product Name	PLASTIC CONDUIT
Product Type	Braided Sleeve
Temperature Range	-58 to 302 °F -50 to 150 °C
UPC	786209882516

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	CPS3G-100-CV0
Instructions and Manuals	CPS3G-100-CV0

Classifications

ETIM 6	EC001937 - Cable protection for installation duct
ETIM 7	EC001937 - Cable protection for installation duct
UNSPSC	39131602
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5392 >> Expandable braided sleeving

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

