

PRODUCT-DETAILS

CPS40B-50-CV0

B. SLEEV. CONFORMED V0, 50M



General Information

Extended Product Type	CPS40B-50-CV0
Product ID	7TCG054800R0077
EAN	5414363149736
Catalog Description	B. SLEEV. CONFORMED V0, 50M
Long Description	Flame Retardant Braided Sleeve, Black Polyester for Temperatures up to 150 Celsius (302 F), Nominal Diameter 40mm (1.57 Inches), Expandable Diameter Range 30mm (1.18 Inches) to 50mm (1.97 Inches), Mini-Reel Length 50m (164.04 Feet)

Ordering

EAN	5414363149736
-----	---------------

Dimensions

Product Net Depth / Length	164.04 ft 50 m
Product Net Weight	3.65 lb 1.655 kg

Container Information

Package Level 1 Units	1 reel
Package Level 2 Units	5 reel

Package Level 2 Width	14.76 in 375 mm
Package Level 2 Height	13.78 in 350 mm
Package Level 2 Depth / Length	29.53 in 750 mm

Additional Information

Brand / Label	Catamount
Bundle Diameter	0.04 to 2.6 in 1 to 66 mm
Color	Black
Material	Polyester
Number of Batteries	0
Product Name	Plastic conduit
Product Type	Braided Sleeve
Temperature Range	-58 to 302 °F -50 to 150 °C
UPC	786210927244

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	CPS40B-50-CV0
Instructions and Manuals	CPS40B-50-CV0

Classifications

ETIM 6	EC001937 - Cable protection for installation duct
ETIM 7	EC001937 - Cable protection for installation duct
UNSPSC	39131602
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5392 >> Expandable braided sleeving

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

