

PRODUCT-DETAILS

CPS6G-100-CV0

GREY SLEEVE CONF. V0, 100M



General Information

Extended Product Type	CPS6G-100-CV0
Product ID	7TCG054800R0102
EAN	5414363406945
Catalog Description	GREY SLEEVE CONF. V0, 100M
Long Description	Flame Retardant Braided Sleeve, Gray Polyester for Temperatures -50 Degrees Celsius (-58 F) up to 150 Celsius (302 F), Nominal Diameter 6mm (0.236 Inches), Expandable Diameter Range 5mm (0.197 Inches) to 11mm (0.433 Inches), Mini-Reel Length 100m (328.08 Feet)

Ordering

EAN	5414363406945
-----	---------------

Dimensions

Product Net Depth / Length	328.08 ft 100 m
Product Net Weight	1.44 lb 653.061 g

Container Information

Package Level 1 Units	1 reel
Package Level 1 Width	7.48 in

	190 mm
Package Level 1 Height	4.33 in
	110 mm
Package Level 1 Depth / Length	7.48 in
	190 mm
Package Level 2 Units	5 reel
Package Level 2 Width	14.76 in
	375 mm
Package Level 2 Height	13.58 in
	345 mm
Package Level 2 Depth / Length	29.53 in
	750 mm

Additional Information

Brand / Label	Catamount
Bundle Diameter	0.04 to 2.6 in 1 to 66 mm
Color	Gray
Material	Polyester
Number of Batteries	0
Product Name	OTHER BRAIDED SLEEVING
Product Type	Braided Sleeve
Temperature Range	-58 to 302 °F -50 to 150 °C
UPC	786209889409

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	CPS6G-100-CV0
Instructions and Manuals	CPS6G-100-CV0

Classifications

ETIM 6	EC001937 - Cable protection for installation duct
ETIM 7	EC001937 - Cable protection for installation duct
UNSPSC	39131602
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5392 >> Expandable braided sleeving

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

