



Price\* : 1,175.07 GBP



## Main

|                                          |                                                                                                                         |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Range                                    | TeSys                                                                                                                   |
| Product name                             | TeSys F                                                                                                                 |
| Product or component type                | Magnetic latching contactor                                                                                             |
| Device short name                        | CR1F                                                                                                                    |
| Device application                       | Control                                                                                                                 |
| Contactor application                    | Resistive load<br>Motor control                                                                                         |
| Utilisation category                     | AC-3<br>AC-1<br>AC-4                                                                                                    |
| Poles description                        | 3P                                                                                                                      |
| Power pole contact composition           | 3 NO                                                                                                                    |
| [Ue] rated operational voltage           | 1000 V AC 25...200 Hz                                                                                                   |
| [Ie] rated operational current           | 265 A (at <40 °C) at <= 440 V AC AC-3<br>350 A (at <40 °C) at <= 440 V AC AC-1<br>245 A (at <40 °C) at <= 440 V AC AC-4 |
| Motor power kW                           | 132 kW at 400 V AC 50/60 Hz (AC-4)                                                                                      |
| Control circuit type                     | AC at 50...400 Hz<br>DC standard                                                                                        |
| [Uc] control circuit voltage             | 127 V AC 50...400 Hz<br>127 V DC                                                                                        |
| Irms rated making capacity               | 2940 A                                                                                                                  |
| Rated breaking capacity                  | 2450 A at 220...440 V<br>2200 A at 500 V<br>800 A at 1000 V<br>1700 A at 660/690 V                                      |
| [Icw] rated short-time withstand current | 2200 A 40 °C - 1 s<br>2200 A 40 °C - 5 s<br>2200 A 40 °C - 10 s<br>1230 A 40 °C - 30 s<br>950 A 40 °C - 1 min           |

|                               |                                                                                                                                                                 |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                               | 620 A 40 °C - 3 min<br>480 A 40 °C - 10 min                                                                                                                     |
| Associated fuse rating        | 315 A aM at <= 440 V<br>400 A BS88 at <= 440 V<br>400 A gG at <= 440 V                                                                                          |
| Average impedance             | 0.32 mOhm - lth 350 A 50 Hz                                                                                                                                     |
| [Ui] rated insulation voltage | 1000 V conforming to IEC 60158-1<br>1000 V conforming to IEC 60947-4<br>1000 V conforming to BS 775<br>1500 V conforming to VDE 0110 group C                    |
| Power dissipation per pole    | 22 W AC-3<br>39 W AC-1                                                                                                                                          |
| Connections - terminals       | Lugs-ring terminals 1 cable(s) 240 mm²<br>Connector 1 cable(s) 240 mm²<br>Bars 2 cable(s) - busbar cross section: 32 x 4 mm<br>Power circuit: bolted connection |
| Tightening torque             | 35 N.m                                                                                                                                                          |
| Operating time                | 40...75 ms latching<br>50...100 ms unlatching                                                                                                                   |
| Mechanical durability         | 1 Mcycles                                                                                                                                                       |
| Maximum operating rate        | 120 cyc/h 40 °C                                                                                                                                                 |

## Complementary

|                                |                                                                                                                  |
|--------------------------------|------------------------------------------------------------------------------------------------------------------|
| Control circuit voltage limits | Latching: 0.85...1.1 Uc<br>Unlatching: 0.85...1.1 Uc                                                             |
| Average consumption            | 1800 VA AC 50...400 Hz latching<br>12 VA AC 50...400 Hz unlatching<br>1800 VA DC latching<br>12 VA DC unlatching |

## Environment

|                                       |                |
|---------------------------------------|----------------|
| Protective treatment                  | TC             |
| Ambient air temperature for operation | -15...70 °C    |
| Ambient air temperature for storage   | -60...80 °C    |
| Operating altitude                    | 3000 m without |
| Height                                | 203 mm         |
| Width                                 | 201.5 mm       |
| Depth                                 | 213 mm         |
| Product weight                        | 7.4 kg         |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|