# Product datasheet Characteristics

## **DF141V**

Fuse carrier TeSys DF, 1P 50A, fuse size 14x51 mm, blown fuse indicator

Price\* : 11.60 GBP



TeSys	
•	
TeSys DF	
Fuse carrier	
DF14	
DF2EA fuse cartridge DF2EN fuse cartridge	
1P	
14 x 51 mm	
, aM , gG	
Toggle	
Blown fuse indication	
690 V AC 690 V DC	
50 A	
690 V AC	
8 kV	
15 kA with tubular links conforming to IEC 60269-1	
120 kA 400 V conforming to IEC 60947-3 120 kA 500 V conforming to IEC 60947-3 80 kA 690 V conforming to IEC 60947-3	
	Fuse carrier  DF14  DF2EA fuse cartridge DF2EN fuse cartridge  1P  14 x 51 mm  , aM , gG  Toggle  Blown fuse indication  690 V AC 690 V DC  50 A  690 V AC 8 kV  15 kA with tubular links conforming to IEC 60269-1  120 kA 400 V conforming to IEC 60947-3 120 kA 500 V conforming to IEC 60947-3

#### Complementary

		;
Standards	EN/IEC 60947-3 EN/IEC 60269-2	70
	UL 4248-1	2
	CSA C22.2 No 4248-1	•
Product certifications	IEC	2.
	UL recognized	
	CSA	
	EAC	
Mounting support	35 mm symmetrical DIN rail	- <del> </del>
Mounting position	Vertical (tolerance: +/- 23°)	
Connections - terminals	Screw clamp terminals 1 cable(s) 2.525 mm²rigid	

Screw clamp terminals 2 cable(s) 2.510 mm²rigid
Screw clamp terminals 1 cable(s) 2.525 mm²flexible with or without
Screw clamp terminals 2 cable(s) 2.510 mm²flexible with or without

Tightening torque	3.5 N.m	
Height	110.8 mm	
Width	26.5 mm	
Depth	76.5 mm	
Product weight	0.143 kg	
Quantity per set	Set of 6	

#### Environment

Ambient air temperature for storage	-4080 °C
Ambient air temperature for operation	-2060 °C with derating above 20°C
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH
Fire resistance	960 °C conforming to IEC 60695-2-1
Compatibility code	DF14

#### Offer Sustainability

REACh Declaration	
Yes	
Compliant EU RoHS Declaration	
Yes	
Yes	
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

### Contractual warranty

Warranty 18 months	
--------------------	--