Product datasheet Characteristics

DF14N

Fuse carrier TeSys DF, Neutral 50A, fuse size 14x51 mm, with tubular link

Price*: 9.09 GBP



Main		
Range	TeSys	
Product name	TeSys DF	
Product or component type	Fuse carrier	
Device short name	DF14	
Device composition	tubular link for locked in Neutral pole	
Poles description	1N	
Fuse size	14 x 51 mm	
Fuse type	, gG , aM	
Control type	Toggle	
[Ue] rated operational voltage	690 V AC 690 V DC	
[le] rated operational current	50 A	
[Ui] rated insulation voltage	690 V AC	
[Uimp] rated impulse withstand voltage	8 kV	
[lpk] rated peak withstand current	15 kA with tubular links conforming to IEC 60269-1	
Short-circuit withstand	120 kA 400 V conforming to IEC 60947-3 120 kA 500 V conforming to IEC 60947-3 80 kA 690 V conforming to IEC 60947-3	

Complementary

o o mpromonton y		
Standards	EN/IEC 60947-3 EN/IEC 60269-2 UL 4248-1 CSA C22.2 No 4248-1	
Product certifications	IEC UL recognized when associated with a phase fuse carrier CSA EAC	
Mounting support	35 mm symmetrical DIN rail	
Mounting position	Vertical (tolerance: +/- 23°)	
Connections - terminals	Screw clamp terminals 1 cable(s) 2.525 mm²rigid Screw clamp terminals 2 cable(s) 2.510 mm²rigid Screw clamp terminals 1 cable(s) 2.525 mm²flexible with or without	

Screw clamp terminals 2 cable(s) 2.5...10 mm²flexible with or without

Tightening torque	3.5 N.m	
Height	110.8 mm	
Width	26.5 mm	
Depth	76.5 mm	
Product weight	0.150 kg	
Quantity per set	Set of 6	

Environment

Ambient air temperature for storage	-4080 °C
Ambient air temperature for operation	-2060 °C with derating above 20°C
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH
Fire resistance	960 °C conforming to IEC 60695-2-1
Compatibility code	DF14

Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months	