


DF2101



Power supply module for electronic circuit breaker

Fuse/IO-Link/24VDC/Module



- 1 panel for labelling
- 2 status LED
- 3 push-in terminals IO-Link
- 4 push-in terminal 0 V
- 5 push-in terminal 24 V DC



Electrical data

Operating voltage	[V]	to SELV/PELV
Nominal voltage DC	[V]	24
Input voltage DC	[V]	19.2...30
Protection class		III
Reverse polarity protection		yes
Mains buffering time (nominal voltage 24 V DC)	[ms]	10
Input current (nominal voltage 24 V DC)	[A]	40
Closed-circuit current	[mA]	10

Interfaces

Communication interface	IO-Link
Min. process cycle time	[ms] 650

Operating conditions

Ambient temperature	[°C] -25...60
Storage temperature	[°C] -40...70
Protection	IP 20; (on the front)
Degree of soiling	2

Tests / approvals

EMC	EN 61000-6-3	radiation of interference
	EN 61000-6-2	noise immunity

DF2101



Power supply module for electronic circuit breaker

Fuse/IO-Link/24VDC/Module

Mechanical data

Weight	[g]	72.8
Dimensions	[mm]	80 x 12.5 x 98

Displays / operating elements

Display	status	LED
---------	--------	-----

Electrical connection

push-in terminals:

contact lever/strip:

Connection

