Product datasheet Characteristics

DF222

Fuse carrier TeSys DF, 2P 125A, fuse size 22x58 mm

Price*: 32.18 GBP



Range	TeSys	
Product name	TeSys DF	
Product or component type	Fuse carrier	
Device short name	DF22	
Product compatibility	DF2FA fuse cartridge DF2FN fuse cartridge	
Poles description	2P	
Fuse size	22 x 58 mm	
Fuse type	, aM , gG	
Control type	Toggle	
[Ue] rated operational voltage	690 V AC 690 V DC	
[le] rated operational current	125 A	
[Ui] rated insulation voltage	690 V AC	
[Uimp] rated impulse withstand voltage	8 kV	
[lpk] rated peak withstand current	19 kA with tubular links conforming to IEC 60269-1	
Short-circuit withstand	120 kA 400 V conforming to IEC 60947-3 120 kA 500 V conforming to IEC 60947-3 80 kA 690 V conforming to IEC 60947-3	
Complementary		
Standards	EN/IEC 60947-3	

Complementary

Complementary		
Standards	EN/IEC 60947-3 EN/IEC 60269-2 UL 4248-1 CSA C22.2 No 4248-1	
Product certifications	IEC UL recognized CSA EAC	
Mounting support	35 mm symmetrical DIN rail	
Mounting position	Vertical (tolerance: +/- 23°)	
Connections - terminals	Screw clamp terminals 1 cable(s) 2.535 mm²rigid Screw clamp terminals 2 cable(s) 2.525 mm²rigid Screw clamp terminals 1 cable(s) 2.535 mm²flexible with or without	

Screw clamp terminals 2 cable(s) 2.5...25 $\text{mm}^2\text{flexible}$ with or without

Tightening torque	4 N.m
Height	127.5 mm
Width	70 mm
Depth	76.5 mm
Product weight	0.436 kg
Quantity per set	Set of 3

Environment

Ambient air temperature for storage	-4080 °C
Ambient air temperature for operation	-2060 °C with derating above 20°C
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH
Fire resistance	960 °C conforming to IEC 60695-2-1
Compatibility code	DF22

Offer Sustainability

REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Compliant EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		

Contractual warranty

Warranty	18 months	