




Compact evaluation unit for speed monitoring

DIA2010-ZROA/50-3000 I/MIN

Status Archive

DI0101



Application

Application	simple evaluation of rotating and linear movement with regard to underspeed; blocking
-------------	---

Electrical data

Nominal voltage AC	[V]	20...250
Nominal voltage DC	[V]	20...250
Reverse polarity protection		no

Outputs

Total number of outputs		1
Output function		normally open
Max. voltage drop switching output DC	[V]	6.5
Minimum load current	[mA]	6
Max. leakage current	[mA]	1.5
Permanent current rating of switching output AC	[mA]	250; (350 AC (...50 °C))
Permanent current rating of switching output DC	[mA]	100
Short-time current rating of switching output	[mA]	2200
Short-circuit proof		no
Overload protection		no

Detection zone

Sensing range	[mm]	10
Sensing range adjustable		no

Measuring/setting range

Setting range	[Imp/min]	50...3000
---------------	-----------	-----------

Accuracy / deviations

Correction factor		steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3
Hysteresis	[% of Sr]	10

DI0002



Compact evaluation unit for speed monitoring

DIA2010-ZROA/50-3000 I/MIN

Response times		
Start-up delay	[s]	12
Max. damping frequency	[Imp/min]	4000
Software / programming		
Adjustment of the switch point		multiturn potentiometer
Operating conditions		
Ambient temperature	[°C]	-25...80
Protection		IP 67
Tests / approvals		
MTTF	[years]	347
Mechanical data		
Weight	[g]	242
Mounting		flush mountable
Dimensions	[mm]	M30 x 1.5 / L = 81
Thread designation		M30 x 1.5
Materials		brass special coating; PBT
Displays / operating elements		
Display	switching status	1 x LED, green
Electrical connection		
Required protection		miniature fuse to IEC60127-2 sheet 1; ≤ 2 A; fast acting
Remarks		
Remarks		Recommendation Check the safe functioning of the unit after a short circuit.

DI0002



Compact evaluation unit for speed monitoring

DIA2010-ZROA/50-3000 I/MIN

Electrical connection

Cable: 2 m, PVC; 2 x 0.5 mm²

Connection



Note miniature fuse to IEC60127-2 sheet 1 ≤ 2 A (fast acting)

Core colours :

BN = brown

BU = blue

Status Archive

DI0101