




Compact speed monitor M12

DFK33,5BWRKG/IO/US



Application

Application	simple evaluation of rotating and linear movement with regard to underspeed; blocking
-------------	---

Electrical data

Nominal voltage DC	[V]	10...30
Current consumption	[mA]	< 10
Protection class		III
Reverse polarity protection		yes

Outputs

Electrical design		PNP/NPN
Output function		normally open / normally closed; (parameterisable)
Max. voltage drop switching output DC	[V]	2.5
Short-time current rating of switching output	[mA]	100; ((20 ms / 0,5 Hz))
Short-circuit proof		yes
Overload protection		yes

Detection zone

Sensing range	[mm]	3.5
Sensing range adjustable		no
Operating distance	[mm]	0...2.83

Measuring/setting range

Setting range	[Imp/min]	5...24000
---------------	-----------	-----------

Accuracy / deviations

Correction factor		steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3
Hysteresis	[% of Sr]	10

Response times

Start-up delay	[s]	0...30; (In steps of: 100 ms; Default: 15 s)
Max. damping frequency	[Imp/min]	30000


Interfaces

Communication interface		IO-Link
-------------------------	--	---------



Compact speed monitor M12



DFK33,5BWRKG/IO/US

Operating conditions		
Ambient temperature	[°C]	-40...85
Protection		IP 66; IP 67; IP 68; IP 69K
Tests / approvals		
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-6 HF conducted	10 V
	EN 55011	class B
	EN 60947-5-2	
Shock resistance	EN 60068-2-27 Ea	100 g 11 ms half-sine; 3 shocks each in every direction of the 3 coordinate axes
Vibration resistance	DIN EN 60947-5-2	20 g (10...3000 Hz)
		50 sweep cycles per frequency; 1 octave per minute in 3 axes
MTTF	[years]	668
UL approval	UL Approval no.	A008
Mechanical data		
Weight	[g]	27.6
Housing		threaded type
Mounting		flush mountable
Dimensions	[mm]	M12 x 1 / L = 60
Thread designation		M12 x 1
Materials		brass white bronze coated; sensing face: PBT orange; LED window: PEI; lock nuts: brass white bronze coated
Displays / operating elements		
Display	SIO mode	
	output stage supplied with current	4x LED, yellow
	IO-Link mode	
	target in measuring range	4x LED, yellow
	target outside measuring range	4x LED, yellow flashing light
Accessories		
Accessories (supplied)		lock nuts: 2
Electrical connection		
Connector: 1 x M12		
		

Compact speed monitor M12

DFK33,5BWRKG/IO/US

Connection



4: OUT / IO-Link