Product datasheet Characteristics

DL1BKB5 AMBER, FLASHING LED, 24VAC/DC





| Main | | - C |
|---------------------------------------|---|----------------|
| Range compatibility | Harmony XVB Harmony XVD Harmony XVP | Ls for specifi |
| Accessory / separate part designation | Protected LED bulb | — <u>- 1</u> |
| Accessory / separate part type | LED bulb | _ ld est |
| Accessory / separate part category | Lighting accessories | of the |
| Accessory / separate part destination | Beacon and indicator bank | _ ville |
| [Us] rated supply voltage | 24 V AC/DC | relia – |
| Signalling type | Flashing | _ o ⊒ii |
| Signalling colour | Orange | |
| Sale per indivisible quantity | 1 | – s puir |
| | | |

Complementary

| Current consumption | 47 mA | 9 |
|---------------------|----------|---|
| Bulb base | BA 15d | |
| Product weight | 0.015 kg | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|---|--|
| REACh Regulation | REACh Declaration | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | Yes | |
| China RoHS Regulation | China RoHS declaration | |
| Environmental Disclosure | Product Environmental Profile | |
| Circularity Profile | No need of specific recycling operations | |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins | |

Warranty 18 months