




Switched-mode power supply 24 V DC

POWER SUPPLY/24VDC/4A/CLASS 2

Status Archive




Electrical data		
Nominal voltage AC	[V]	< 230
Nominal frequency AC	[Hz]	47...63
Input voltage DC	[V]	210...375
Input voltage AC	[V]	85...132 / 176...264
Protection class		I; (IEC 61140)
Max. power-on delay time	[ms]	20
Power-on delay time	[s]	< 20
Output voltage tolerance	[%]	1...5
Max. output current at min. output voltage	[A]	4
Number of output circuits		1
Max. residual ripple	[%]	0.1
Derating	[W/K]	3 (60...70 °C)
Outputs		
Short-circuit protection		yes
Overload protection		yes
Operating conditions		
Ambient temperature	[°C]	-10...60
Protection		IP 20



Switched-mode power supply 24 V DC

POWER SUPPLY/24VDC/4A/CLASS 2

Tests / approvals		
EMC	EN 50081-1	
	EN 61000-6-2	
MTTF	[years]	260
Mechanical data		
Weight	[g]	696
Type of mounting		rail; (TH35 (EN 60715))
Dimensions	[mm]	131 x 65 x 107
Materials		aluminium
Displays / operating elements		
Display	Output voltage	LED, green
Remarks		
Notes	discontinued article	
Pack quantity	1 pcs.	
Electrical connection		
terminals: 1.5...6 mm²		
Connection		



Status Archive