


E11432



Jumper cable with valve plug

VVSAB031MSS00,6H03STGH030MSS



Application

Free from silicone ☐ yes

Electrical data

Operating voltage [V] ☐ < 24 AC/DC

Overvoltage protection ☐ yes; (VDR)

Max. current load total [A] ☐ 3

Operating conditions

Ambient temperature [°C] ☐ -25...80

Protection ☐ IP 67

Mechanical data

Weight [g] ☐ 70.6

Materials ☐ PUR

Material nut ☐ brass / brass

Displays / operating elements

Display ☐ switching status ☐ 1 x LED, yellow

Accessories

Accessories (supplied) ☐ screw
☐ panel for labelling

Remarks

Pack quantity ☐ 1 pcs.



Jumper cable with valve plug

VVSAB031MSS00,6H03STGH030MSS

Electrical connection

Cable: 0.6 m, PUR, Halogen-free, black, Ø 5 mm; 3 x 0.5 mm² (42 x Ø 0.1 mm)


Electrical connection - socket

Connector: 1 x valve type B industrial standard, angled; Moulded body: PUR; Locking: brass, nickel-plated; Contacts: nickel-plated brass; Tightening torque: 0.7...0.9 Nm



Electrical connection - plug

Connector: 1 x M12, straight; Moulded body: PUR; Locking: brass, nickel-plated; Contacts: gold-plated; Tightening torque: 0.7...0.9 Nm



Connection

