


E11806



Connecting cable with socket

ADOAH080MSS0010C08



Application

Free from silicone	yes
--------------------	-----

Electrical data

Operating voltage [V]	< 30 AC / < 36 DC
Protection class	III

Operating conditions

Ambient temperature [°C]	-25...80
Protection	IP 67

Mechanical data

Weight [g]	676.8
Dimensions [mm]	28 x 15 x 38
Materials	PUR
Material nut	brass

Remarks

Notes	For 8-pole sockets the core colours are not standardised.; Please note the wiring of the sensor and the sockets (see data sheet).
Pack quantity	1 pcs.

Electrical connection

Cable: 10 m, PUR, Halogen-free, black, Ø 6.2 mm, shielded; 8 x 0.25 mm²

Electrical connection - socket


Connector: 1 x M12, angled; Moulded body: PUR; Locking: brass, nickel-plated; Contacts: gold-plated; Tightening torque: 0.7...0.9 Nm; Shielded connection cable: screen connected

E11806




Connecting cable with socket

ADOAH080MSS0010C08



Connection



colours to DIN EN 60947-5-2

Core colours :

BK =	black
BN =	brown
BU =	blue
GY =	grey
PK =	pink
OG =	orange
VT =	lilac
WH =	white
screen =	screen