


E12332



Connection cable

VDOGH040MSS0015C04STGH040MSS




Application		
Free from silicone		yes
Electrical data		
Operating voltage	[V]	< 50 AC / < 60 DC
Protection class		III
Max. current load total	[A]	4
Operating conditions		
Ambient temperature	[°C]	-25...85
Protection		IP 68
Mechanical data		
Weight	[g]	655.6
Dimensions	[mm]	14.5 x 14.5 x 48.5
Materials		PUR
Material nut		diecast zinc / diecast zinc
Remarks		
Pack quantity		1 pcs.
Electrical connection		
Cable: 15 m, PUR, Halogen-free, black, Ø 5 mm, shielded; 4 x 0.34 mm ² (42 x Ø 0.1 mm)		
Electrical connection - socket		
Connector: 1 x M12, straight; Moulded body: PUR; Locking: diecast zinc, nickel-plated; Contacts: gold-plated; Tightening torque: 0.7...0.9 Nm		

E12332



Connection cable

VDOGH040MSS0015C04STGH040MSS



Electrical connection - plug

Connector: 1 x M12, straight; Moulded body: PUR; Locking: diecast zinc, nickel-plated; Contacts: gold-plated; Tightening torque: 0.7...0.9 Nm



Connection

