


E12336



Connection cable

VDOGH040MSS0004H04STGX040--S



Application

Free from silicone	yes
--------------------	-----

Electrical data

Operating voltage [V]	10...36 DC
Protection class	II
Max. current load total [A]	4

Operating conditions

Ambient temperature [°C]	-25...90
Protection	IP 67

Mechanical data

Weight	[g]	176.4	
Materials		socket housing: TPU orange; Sealing: FKM	
Material nut		brass / brass	
Drag chain suitability		bending radius for flexible use	min. 10 x cable diameter
		travel speed	max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s²
		bending cycles	> 5 Mio.
		torsional strain	± 180 °/m
Drag chain suitability		yes	

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

Cable: 4 m, PUR, Halogen-free, black, Ø 5.1 mm; 4 x 0.50 mm² (64 x Ø 0.1 mm)

Electrical connection - socket


Connector: 1 x M12, straight; Locking: brass, nickel-plated; Contacts: nickel-plated; Tightening torque: 0.6...1.5 Nm

E12336



Connection cable

VDOGH040MSS0004H04STGX040--S



Electrical connection - plug

Connector: 1 x DEUTSCH connector, straight; Locking: brass, nickel-plated; Contacts: gold-plated; Tightening torque: 0.6...1.5 Nm



Connection

