


E12362



Connecting cable with socket

ADOAH080MSS0001H08




Application		
Free from silicone		yes
Electrical data		
Operating voltage	[V]	< 30 AC / < 36 DC
Protection class		III
Max. current load total	[A]	2; (...40 °C)
Operating conditions		
Ambient temperature	[°C]	-25...80
Protection		IP 67
Mechanical data		
Weight	[g]	77.2
Dimensions	[mm]	28 x 15 x 38
Materials		PUR
Material nut		brass
Remarks		
Notes	For 8-pole sockets the core colours are not standardised.; Please note the wiring of the sensor and the sockets (see data sheet).	
Pack quantity		1 pcs.
Electrical connection		
Cable: 1 m, PUR, Halogen-free, black, Ø 6.2 mm; 8 x 0.25 mm²		
Electrical connection - socket		
Connector: 1 x M12, angled; Moulded body: PUR; Locking: brass, nickel-plated; Contacts: gold-plated; Tightening torque: 0.7...0.9 Nm		

E12362



Connecting cable with socket

ADOAH080MSS0001H08



Connection

1	BN
2	WH
3	BU
4	BK
5	GY
6	PK
7	VT
8	OG

colours to DIN EN 60947-5-2

Core colours :

BK =	black
BN =	brown
BU =	blue
GY =	grey
PK =	pink
OG =	orange
VT =	lilac
WH =	white