


E3M151



Connection cable

CONNECTION CABLE M12 5M




Application		
Design	for 3D Smart sensor mobile with analogue video output PAL	
Electrical data		
Operating voltage	[V]	< 50 AC / < 60 DC
Protection class	III	
Operating conditions		
Ambient temperature	[°C]	-40...80
Protection	IP 67; IP 69K	
Mechanical data		
Weight	[g]	271.4
Materials	housing: PUR; Sealing: FKM; contact pins: CuSn6 nickel-plated and tin-plated;	
Material nut	stainless steel (1.4305 / 303) / stainless steel (1.4305 / 303)	
Drag chain suitability	bending radius for fixed installation	≥ 60 mm
Remarks		
Pack quantity	1 pcs.	
Electrical connection		
Cable: 5 m, TPU, black, Ø 6 mm, shielded; 3 x 0.25 mm²		
Electrical connection - plug		
Connector: 1 x M12, straight; Locking: stainless steel (1.4305 / 303)		
Connector: 1 x M12, angled; Locking: stainless steel (1.4305 / 303)		

E3M151




Connection cable

CONNECTION CABLE M12 5M



Connection



- | | |
|----|-----------------|
| 1: | screen |
| 2: | not used |
| 3: | coax screen |
| 4: | coax cable core |
| 5: | not used |