


E80343



RFID tag

ID-TAG/90X34x7/06



Electrical data

Operating frequency	[MHz]	13,56
Memory size	[bit]	896
Memory type		EEPROM
Chip type		ICODE SLIX
Number of blocks		28
Block size	[Byte]	4
Unique Identification Number (UID)	[Byte]	8
RFID standard		ISO 15693
Max. read cycles		unlimited
Max. write cycles		100000

Operating conditions

Ambient temperature	[°C]	-25...85
Storage temperature	[°C]	-40...85
Protection		IP 68

Tests / approvals

Shock resistance	DIN IEC 68-2-27	40 g 18 ms
Vibration resistance	DIN IEC 68-2-6	10 g 10...2000 Hz
Radio approval	ISO 15693	

Mechanical data

Weight	[g]	115.2
Type of mounting	Installation on metal and non-metal materials; (screw fastening ; sticking to a surface ; In case of installation on metal mount the flat side on the surface)	
Materials	ABS	

Remarks

Pack quantity	5 pcs.
---------------	--------



RFID tag

ID-TAG/90X34x7/06

Other data

read distance (mm)

ANT410	-
ANT411	5
ANT420 / DTM424 / DTM426	-
ANT421 / DTM425 / DTM427	20
ANT430 / DTM434 / DTM436	15
ANT431 / DTM435 / DTM437	25
ANT513 / DTC510	50
ANT515 / ANT516	20
ANT600	-

read distance when mounted on metal (mm)

ANT410	10
ANT411	15
ANT420 / DTM424 / DTM426	5
ANT421 / DTM425 / DTM427	30
ANT430 / DTM434 / DTM436	25
ANT431 / DTM435 / DTM437	40
ANT513 / DTC510	55
ANT515 / ANT516	25
ANT600	-