


ZDO8H050VAS0015E19



Free from silicone	yes
--------------------	-----

Operating voltage	[V]	10...30 DC; ("supply class 2" to cULus)
Protection class		II
Max. current load per module/slot	[A]	4
Max. current load total	[A]	12


Ambient temperature	[°C]	-25...70
Ambient temperature (moving)	[°C]	-5...60
Protection		IP 67; IP 68; ("enclosure type 1" according to cULus)

EBT004



Splitter box

ZDO8H050VAS0015E19

Mechanical data	
Weight	[g] 2944
Dimensions	[mm] 22 x 54 x 127
Materials	housing: PA
Number of ports splitter box	8
Connector type	M12
Accessories	
Accessories (supplied)	Protective caps: 2
	labels: 8
Remarks	
Pack quantity	1 pcs.
Electrical connection	
Cable: 15 m, PVC, black, Ø 9.7 mm; 16 x 0.34 mm ² + 3 x 1.0 mm ²	
Electrical connection - slot	
Connector: 8 x M12; Contacts: gold-plated; Tightening torque: 0.8...1.5 Nm	
	



Splitter box

ZDO8H050VAS0015E19

Connection

<u>BN</u>	1 (1...8)	C
<u>BU</u>	3 (1...8)	C
<u>GN/YE</u>	5 (1...8)	C
<u>GY/PK</u>	2 (1)	C
<u>RD/BU</u>	2 (2)	C
<u>WH/GN</u>	2 (3)	C
<u>BN/GN</u>	2 (4)	C
<u>WH/YE</u>	2 (5)	C
<u>YE/BN</u>	2 (6)	C
<u>WH/GY</u>	2 (7)	C
<u>GY/BN</u>	2 (8)	C
<u>WH</u>	4 (1)	C
<u>GN</u>	4 (2)	C
<u>YE</u>	4 (3)	C
<u>GY</u>	4 (4)	C
<u>PK</u>	4 (5)	C
<u>RD</u>	4 (6)	C
<u>BK</u>	4 (7)	C
<u>VT</u>	4 (8)	C

Core colours :

BK =	black
BN =	brown
BU =	blue
GN =	green
GY =	grey
PK =	pink
RD =	red
VT =	lilac
WH =	white
YE =	yellow

EBT004

Splitter box

ZDO8H050VAS0015E19

