

EVC27A



Connecting cable with socket

ADOAH040VAT0020H04/3G/2D



Application

Compatible with paint	yes
-----------------------	-----

Electrical data

Operating voltage [V]	< 60 AC/DC
Protection class	II
Max. current load total [A]	2

Operating conditions

Ambient temperature [°C]	-20...60
Protection	IP 67; (outside hazardous areas: IP 68 / IP 69K)

Tests / approvals

Approval	BVS 08 ATEX E 109 U; IECEx BVS 08.0041 U
ATEX marking	 II 3G Ex nA IIC Gc
	 II 2D Ex tb IIIC Db IP65/IP67

Mechanical data

Weight [g]	660
Dimensions [mm]	26.5 x 15.5 x 36.5
Materials	housing: TPU orange; Sealing: FKM
Material nut	stainless steel (1.4404 / 316L)

Remarks

Pack quantity	1 pcs.
---------------	--------

EVC27A



Connecting cable with socket


ADOAH040VAT0020H04/3G/2D

Electrical connection


Cable: 20 m, PUR, Halogen-free, black, Ø 4.9 mm; 4 x 0.34 mm² (42 x Ø 0.1 mm)

Electrical connection - socket

Connector: 1 x M12, angled; Locking: stainless steel (1.4404 / 316L); Contacts: gold-plated; Tightening torque: 1.2...1.5 Nm



Connection



	Core colours :
BK =	black
BN =	brown
BU =	blue
WH =	white