


EVC681



Connection cable

VDOGH046MSS00,3H04STGH040MSS



Application

Free from silicone yes

Electrical data

Operating voltage [V] 10...36 DC

Protection class II

Max. current load total [A] 4

Outputs

Electrical design PNP

Operating conditions

Ambient temperature [°C] -25...90

Note on ambient temperature cULus: ...75 °C

Ambient temperature (moving) [°C] -25...90

Note on ambient temperature (moving) cULus: ...75 °C


Protection IP 65; IP 67; IP 68; IP 69K

EVC681



Connection cable

VDOGH046MSS00,3H04STGH040MSS

Mechanical data		
Weight	[g]	43.2
Materials	connector housing: TPU orange; socket housing: TPU black transparent; Sealing: FKM	
Material nut	brass / brass	
Drag chain suitability	bending radius for flexible use	min. 10 x cable diameter
	travel speed	max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s²
	bending cycles	> 5 Mio.
	torsional strain	± 180 °/m
Drag chain suitability	yes	
Displays / operating elements		
Display	switching status	4 x LED, yellow
	operation	2 x LED, green
Remarks		
Pack quantity	1 pcs.	
Electrical connection		
Cable: 0.3 m, PUR, Halogen-free, black, Ø 4.9 mm; 4 x 0.34 mm² (42 x Ø 0.1 mm)		
Electrical connection - socket		
Connector: 1 x M12, straight; Locking: brass, nickel-plated; Contacts: gold-plated; Tightening torque: 0.6...1.5 Nm		
		
Electrical connection - plug		
Connector: 1 x M12, straight; Locking: brass, nickel-plated; Contacts: gold-plated; Tightening torque: 0.6...1.5 Nm		
		

EVC681



Connection cable

VDOGH046MSS00,3H04STGH040MSS

Connection

