


EVC710



Connecting cable with socket

ADOGH040MSP0050H04



Application

Free from silicone yes

Electrical data

Operating voltage [V] < 250 AC / < 300 DC

Protection class II

Max. current load total [A] 4

Operating conditions

Ambient temperature [°C] -25...90

Ambient temperature (moving) [°C] -25...90

Protection IP 65; IP 67; IP 68; IP 69K

Mechanical data

Weight [g] 319

Dimensions [mm] 15.5 x 15.5 x 45

Materials housing: TPU orange; Sealing: FKM

Material nut brass

Drag chain suitability	bending radius for flexible use	min. 10 x cable diameter
	travel speed	max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s ²
	bending cycles	> 5 Mio.
	torsional strain	± 180 °/m

Drag chain suitability yes

Remarks

Pack quantity 1 pcs.

EVC710



Connecting cable with socket


ADOGH040MSP0050H04

Electrical connection


Cable: 50 m, PUR, Halogen-free, black, Ø 6.2 mm; 4 x 1.00 mm² (32 x Ø 0.2 mm)

Electrical connection - socket

Connector: 1 x M12, straight; Locking: brass, nickel-plated; Contacts: gold-plated; Tightening torque: 0.6...1.5 Nm



Connection



Core colours :

BK =	black
BN =	brown
BU =	blue
WH =	white