

PRODUCT-DETAILS

EXBBT0720

LFH-EMC BRAIDED FLEX 40MM COND 20M



General Information

Extended Product Type	EXBBT0720
Product ID	7TCA297120R0454
EAN	5011949243286
Catalog Description	LFH-EMC BRAIDED FLEX 40MM COND 20M
Long Description	Liquid Tight Metallic Conduit, Low Fire Hazard with EMC Protection, Conduit Size 40mm, Minimum Bore 35.3mm, Reel Length 20 Meters, Galvanised Steel Core with Low Toxicity Covering, Black

Additional Information

Application	Connection for Conduit Systems when Low Fire Hazard is Needed
Product Type	Liquid Tight Metallic Conduit

Ordering

EAN	5011949243286
UPC	786210316413
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	20 m
----------------------------	------

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Low Toxicity Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	16 in 406 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	EXBBT0720
Instructions and Manuals	EXBBT0720
Declaration of Conformity - CE	9AKK107492A9617

Classifications	
UNSPSC	39131706

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems	

