

PRODUCT-DETAILS

EXBBT0810

EMC SCREENED LT 50MM



General Information

Extended Product Type	EXBBT0810
Product ID	7TCA297120R0439
EAN	5011949241503
Catalog Description	EMC SCREENED LT 50MM
Long Description	Liquid Tight Metallic Conduit, Low Fire Hazard with EMC Protection, Conduit Size 50mm, Minimum Bore 40.4mm, Reel Length 10 Meters, Galvanised Steel Core with Low Toxicity Covering, Black

Additional Information

Application	Connection for Conduit Systems when Low Fire Hazard is Needed
Product Type	Liquid Tight Metallic Conduit

Ordering

EAN	5011949241503
UPC	786210309125
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	10 m
----------------------------	------

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Low Toxicity Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth / Length	1 in 25 mm
Package Level 1 Width	1 in 25 mm

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	EXBBT0810
Instructions and Manuals	EXBBT0810
Declaration of Conformity - CE	9AKK107492A9617

Classifications	
UNSPSC	39131706

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems	

