

PRODUCT-DETAILS

EXBBT0820

FLEXIBLE CONDUIT 50MM EMC



General Information

Extended Product Type	EXBBT0820
Product ID	7TCA297120R0470
EAN	5011949243446
Catalog Description	FLEXIBLE CONDUIT 50MM EMC
Long Description	Liquid Tight Metallic Conduit, Low Fire Hazard with EMC Protection, Conduit Size 50mm, Minimum Bore 40.4mm, Reel Length 20 Meters, Galvanised Steel Core with Low Toxicity Covering, Black

Additional Information

Application	Connection for Conduit Systems when Low Fire Hazard is Needed
Product Type	Liquid Tight Metallic Conduit

Ordering

EAN	5011949243446
UPC	786210316260
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	20 m
----------------------------	------

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Low Toxicity Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	16 in 406 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	EXBBT0820
Instructions and Manuals	EXBBT0820
Declaration of Conformity - CE	9AKK107492A9617

Classifications	
UNSPSC	39131706

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems	

