

PRODUCT-DETAILS

EXLH0620

HIGH TEMP FLEXIBLE CONDUIT 32MM



General Information

Extended Product Type	EXLH0620
Product ID	7TCA297120R0093
EAN	5011949001787
Catalog Description	HIGH TEMP FLEXIBLE CONDUIT 32MM
Long Description	Liquid Tight Metallic Conduit, High Temperature Applications, Conduit Size 32mm, Minimum Bore 26.4mm, Reel Length 20 Meters, Galvanised Steel Core with Chemical Resistant Coating, Black

Additional Information

Application	Connection for Conduit Systems when Flame and Chemical Resistance are Needed
Product Type	Liquid Tight Metallic Conduit

Ordering

EAN	5011949001787
UPC	786210287539
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	20 m
----------------------------	------

Technical

Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Chemical Resistant Coating

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	26 in 660 mm
Package Level 1 Depth / Length	8 in 203 mm
Package Level 1 Width	26 in 660 mm
Package Level 2 Units	1 piece
Package Level 2 Height	7.5 in 191 mm
Package Level 2 Depth / Length	13 in 330 mm
Package Level 2 Width	7.5 in 191 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	EXLH0620
Instructions and Manuals	EXLH0620
Declaration of Conformity - CE	9AKK107492A9617

Classifications

UNSPSC	39131706
--------	----------

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

