

PRODUCT-DETAILS

EXLLH0530

FLEX. CONDUIT 25 MM HIGH TEMP. 30M



General Information

Extended Product Type	EXLLH0530
Product ID	7TCA297120R0124
EAN	5011949001213
Catalog Description	FLEX. CONDUIT 25 MM HIGH TEMP. 30M
Long Description	Liquid Tight Metallic Conduit, High Temperature Applications, Conduit Size 25mm, Minimum Bore 21mm, Reel Length 30 Meters, Galvanised Steel Core with Chemical Resistant Coating, Blue

Additional Information

Application	Connection for Conduit Systems with High Temperature Applications
Product Type	Liquid Tight Metallic Conduit

Ordering

EAN	5011949001213
UPC	786210263670
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	30 m
----------------------------	------

Technical	
Number of Batteries	0
Color	Blue
Material	Galvanized Steel Core with Chemical Resistant Coating

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	26 in 660 mm
Package Level 1 Depth / Length	26 in 660 mm
Package Level 1 Width	1.1 in 28 mm
Package Level 2 Units	1 piece
Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	11 in 279 mm
Package Level 2 Width	17 in 432 mm

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	EXLLH0530
Instructions and Manuals	EXLLH0530
Declaration of Conformity - CE	9AKK107492A9617

Classifications	
UNSPSC	39131706

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems	

