

PRODUCT-DETAILS

# EXLT0430

## LFH FLEXIBLE CONDUIT NC20 30M BLK



### General Information

|                       |                                                                                                                                                            |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | EXLT0430                                                                                                                                                   |
| Product ID            | 7TCA297120R0137                                                                                                                                            |
| EAN                   | 5011949001237                                                                                                                                              |
| Catalog Description   | LFH FLEXIBLE CONDUIT NC20 30M BLK                                                                                                                          |
| Long Description      | Liquid Tight Metallic Conduit, Low Fire Hazard, Conduit Size 20mm, Minimum Bore 16mm, Reel Length 30 Meters, Galvanised Steel Core with LFH Coating, Black |

### Additional Information

|              |                                                               |
|--------------|---------------------------------------------------------------|
| Application  | Connection for Conduit Systems when Low Fire Hazard is Needed |
| Product Type | Liquid Tight Metallic Conduit                                 |

### Ordering

|                       |               |
|-----------------------|---------------|
| EAN                   | 5011949001237 |
| UPC                   | 786210287638  |
| Customs Tariff Number | 8307106000    |

### Dimensions

|                            |      |
|----------------------------|------|
| Product Net Depth / Length | 30 m |
|----------------------------|------|

Technical

|                     |                                                    |
|---------------------|----------------------------------------------------|
| Number of Batteries | 0                                                  |
| Color               | Black                                              |
| Material            | Galvanized Steel Core with Low Fire Hazard Coating |

Environmental

|               |                           |
|---------------|---------------------------|
| WEEE Category | Product Not in WEEE Scope |
|---------------|---------------------------|

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Height         | 1 in<br>25 mm |
| Package Level 1 Depth / Length | 1 in<br>25 mm |
| Package Level 1 Width          | 1 in<br>25 mm |

Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | EXLT0430        |
| Instructions and Manuals          | EXLT0430        |
| Declaration of Conformity - CE    | 9AKK107492A9617 |

Classifications

|        |          |
|--------|----------|
| UNSPSC | 39131706 |
|--------|----------|

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

