

PRODUCT-DETAILS

EXLT0430

LFH FLEXIBLE CONDUIT NC20 30M BLK



General Information

Extended Product Type	EXLT0430
Product ID	7TCA297120R0137
EAN	5011949001237
Catalog Description	LFH FLEXIBLE CONDUIT NC20 30M BLK
Long Description	Liquid Tight Metallic Conduit, Low Fire Hazard, Conduit Size 20mm, Minimum Bore 16mm, Reel Length 30 Meters, Galvanised Steel Core with LFH Coating, Black

Additional Information

Application	Connection for Conduit Systems when Low Fire Hazard is Needed
Product Type	Liquid Tight Metallic Conduit

Ordering

EAN	5011949001237
UPC	786210287638
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	30 m
----------------------------	------

Technical

Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Low Fire Hazard Coating

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth / Length	1 in 25 mm
Package Level 1 Width	1 in 25 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	EXLT0430
Instructions and Manuals	EXLT0430
Declaration of Conformity - CE	9AKK107492A9617

Classifications

UNSPSC	39131706
--------	----------

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

