

PRODUCT-DETAILS

EXLT0720

LFH FLEXIBLE CONDUIT 40MM 20M BLK



General Information

Extended Product Type	EXLT0720
Product ID	7TCA297120R0144
EAN	5011949001985
Catalog Description	LFH FLEXIBLE CONDUIT 40MM 20M BLK
Long Description	Liquid Tight Metallic Conduit, Low Fire Hazard, Conduit Size 40mm, Minimum Bore 35.3mm, Reel Length 20 Meters, Galvanised Steel Core with LFH Coating, Black

Additional Information

Application	Connection for Conduit Systems when Low Fire Hazard is Needed
Product Type	Liquid Tight Metallic Conduit

Ordering

EAN	5011949001985
UPC	786210287676
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	20 m
----------------------------	------

Technical

Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Low Fire Hazard Coating

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth / Length	1 in 25 mm
Package Level 1 Width	1 in 25 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	EXLT0720
Instructions and Manuals	EXLT0720
Declaration of Conformity - CE	9AKK107492A9617

Classifications

UNSPSC	39131706
--------	----------

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

