

PRODUCT-DETAILS

EXLUB0610

UL LIQUID TIGHT CONDUIT NC32, 10M



Product image
not available

General Information

Extended Product Type	EXLUB0610
Product ID	7TCA297120R0430
EAN	5011949241176
Catalog Description	UL LIQUID TIGHT CONDUIT NC32, 10M
Long Description	Liquid Tight, Pliable Conduit, Nominal Conduit Size 32mm, 1 Inch US Trade Size, Inside Diameter 26.4mm, UL E76358, Approved to EN/IEC 60079-0, 60079-7, 60079-31 UL360, Static Bend Radius 165mm, Reel Length 10 Meters, Galvanised Steel Core with PVC Covering and Copper Grounding Wire, Black

Additional Information

Application	Can Be Used with Ex LT Fittings for Ex E Systems or Combination Ex LT and HA-G1 Fittings for Ex D E Systems
Product Type	Liquid Tight Flame Retardant Conduit

Ordering

EAN	5011949241176
UPC	786210309224
Customs Tariff Number	8307106000

Dimensions

Product Net Depth /	10 m
---------------------	------

Length

Technical

Number of Batteries	0
Color	Black
Material	Galvanized Steel Core and Copper Grounding Wire with PVC Covering

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth / Length	1 in 25 mm
Package Level 1 Width	1 in 25 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	EXLUB0610
Instructions and Manuals	EXLUB0610
Declaration of Conformity - CE	9AKK107492A9617

Classifications

UNSPSC	39131706
--------	----------

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available