

## PRODUCT-DETAILS

# EXLUB0720

## UL LIQUID TIGHT CONDUIT 40MM 20M BL



Product image  
not available

### General Information

|                       |                                                                                                                                                                                                                                                                                                       |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | EXLUB0720                                                                                                                                                                                                                                                                                             |
| Product ID            | 7TCA297120R0433                                                                                                                                                                                                                                                                                       |
| EAN                   | 5011949241206                                                                                                                                                                                                                                                                                         |
| Catalog Description   | UL LIQUID TIGHT CONDUIT 40MM 20M BL                                                                                                                                                                                                                                                                   |
| Long Description      | Liquid Tight, Pliable Conduit, Nominal Conduit Size 40mm, 1-1/4 Inch US Trade Size, Inside Diameter 35.3mm, UL E76358, Approved to EN/IEC 60079-0, 60079-7, 60079-31 UL360, Static Bend Radius 200mm, Reel Length 20 Meters, Galvanised Steel Core with PVC Covering and Copper Grounding Wire, Black |

### Additional Information

|              |                                                                                                             |
|--------------|-------------------------------------------------------------------------------------------------------------|
| Application  | Can Be Used with Ex LT Fittings for Ex E Systems or Combination Ex LT and HA-G1 Fittings for Ex D E Systems |
| Product Type | Liquid Tight Flame Retardant Conduit                                                                        |

### Ordering

|                       |               |
|-----------------------|---------------|
| EAN                   | 5011949241206 |
| UPC                   | 786210309200  |
| Customs Tariff Number | 8307106000    |

### Dimensions

|                     |      |
|---------------------|------|
| Product Net Depth / | 20 m |
|---------------------|------|

Length

Technical

|                     |                                                                   |
|---------------------|-------------------------------------------------------------------|
| Number of Batteries | 0                                                                 |
| Color               | Black                                                             |
| Material            | Galvanized Steel Core and Copper Grounding Wire with PVC Covering |

Environmental

|               |                           |
|---------------|---------------------------|
| WEEE Category | Product Not in WEEE Scope |
|---------------|---------------------------|

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Height         | 1 in<br>25 mm |
| Package Level 1 Depth / Length | 1 in<br>25 mm |
| Package Level 1 Width          | 1 in<br>25 mm |

Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | EXLUB0720       |
| Instructions and Manuals          | EXLUB0720       |
| Declaration of Conformity - CE    | 9AKK107492A9617 |

Classifications

|        |          |
|--------|----------|
| UNSPSC | 39131706 |
|--------|----------|

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available