

PRODUCT-DETAILS

FPW516

INSUL PIERCING WASHER CU 5/16 STUD



General Information

Extended Product Type	FPW516
Product ID	7TAI029030R0034
EAN	5414363113379
Catalog Description	INSUL PIERCING WASHER CU 5/16 STUD
Long Description	Insulation Piercing Washer, Outer Diameter 25.4mm (1.0 Inch), Inner Diameter 8.6mm (0.34 Inch), Stud Size 5/16 Inch, Copper Alloy, Tin Plated

Ordering

EAN	5414363113379
-----	---------------

Dimensions

Product Net Length	0, mm
--------------------	-------

Container Information

Package Level 1 Units	250 piece
Package Level 1 Width	3 in 76 mm
Package Level 1 Height	3 in 76 mm
Package Level 1 Depth /	3.5 in

Length	89 mm
Package Level 2 Units	2500 piece
Package Level 2 Width	7.5 in 191 mm
Package Level 2 Height	3.5 in 89 mm
Package Level 2 Depth / Length	16.5 in 419 mm

Additional Information

Application	Enables copper to aluminum connections to be made in a bolted joint without the use of inhibiting compounds.
Brand / Label	Sta-Kon
Effective Date	19890303
Inside Diameter	0.34 in 8.6 mm
Material	Copper
Number of Batteries	0
Outside Diameter	1.0 in 25.4 mm
Product Name	COPPER WASHER
Product Type	Transition Washer
Special Functions	Accommodates the difference in thermal expansion between copper and aluminum and enhances the efficiency of bolted grounding connections.
Standards	UL E9809
Suitable For	5/16 Inch
Surface Finishing	Tin Plated
Thickness	0.035 in 0.89 mm
UPC	786210709956

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	FPW516
Instructions and Manuals	FPW516

Classifications

ETIM 6	EC002345 - Serrated lock washer
ETIM 7	EC002345 - Serrated lock washer
UNSPSC	31161807
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	2885 >> Flat washers

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

