## Product data sheet Characteristics

# GBX0400040571G

gearbox with straight teeth GBX -  $\varnothing$  40 mm - reduction 4:1 - < 24  $^{\circ}$  - 15 N.m

#### Main

Range compatibility	Lexium 05
Product or component type	Planetary gearbox with straight teeth
Device short name	GBX
Product compatibility	BRH0571
Casing diameter	40 mm
Reduction ratio	4:1
Additional information	Lubricated for life

### Complementary

< 24 °
1 Nm/arcmin
Black
Black anodized aluminium
C 45
30000 h at 100 rpm at 30 °C
Any position
96 %
160 N at 100 rpm , force applied at mid-distance from output shaft during 30000 hour at 30 $^{\circ}\text{C}$ 200 N at 100 rpm , force applied at mid-distance from output shaft during 10000 hour at 30 $^{\circ}\text{C}$
160 N at 100 rpm , during 30000 hour at 30°C 200 N at 100 rpm , during 10000 hour at 30°C
0.022 kg.cm²
15 N.m at 100 rpm at 30 °C
24 N.m at 100 rpm at 30 °C
0.35 kg

#### Environment

Noise level	55 dB at 1 m , no-load
IP degree of protection	IP54 at shaft output
Ambient temperature for operation	-2590 °C