

Product data sheet

Characteristics

GBX0600040703F

gearbox with straight teeth GBX - Ø 60 mm -
reduction 4:1 - < 16 ° - 38 N.m

Main

Range compatibility	Lexium 05 Lexium 15
Product or component type	Planetary gearbox with straight teeth
Device short name	GBX
Product compatibility	BSH0703
Casing diameter	60 mm
Reduction ratio	4:1
Additional information	Lubricated for life

Complementary

Torsional backlash	< 16 °
Torsional rigidity	2.3 Nm/arcmin
Housing colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Service life in hours	30000 h at 100 rpm at 30 °C
Mounting position	Any position
Efficiency	96 %
Maximum radial force Fr	340 N at 100 rpm , force applied at mid-distance from output shaft during 30000 hour at 30 °C 500 N at 100 rpm , force applied at mid-distance from output shaft during 10000 hour at 30 °C
Maximum axial force Fa	450 N at 100 rpm , during 30000 hour at 30°C 600 N at 100 rpm , during 10000 hour at 30°C
Moment of inertia	0.093 kg.cm²
Continuous output torque	38 N.m at 100 rpm at 30 °C
Maximum output torque	61 N.m at 100 rpm at 30 °C
Product weight	0.9 kg

Environment

Noise level	58 dB at 1 m , no-load
IP degree of protection	IP54 at shaft output
Ambient temperature for operation	-25...90 °C