Product data sheet Characteristics

GBX0600090703F

gearbox with straight teeth GBX - \emptyset 60 mm - reduction 9:1 - < 20 $^{\circ}$ - 44 N.m

Main Range compatibility Lexium 05 Lexium 15 Product or component type Planetary gearbox with straight teeth type Device short name GBX Product compatibility BSH0703 Casing diameter 60 mm Reduction ratio 9:1

Lubricated for life

Complementary

Torsional backlash	< 20 °
Torsional rigidity	2.5 Nm/arcmin
Housing colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Service life in hours	30000 h at 100 rpm at 30 °C
Mounting position	Any position
Efficiency	94 %
Maximum radial force Fr	$340~N$ at $100~rpm$, force applied at mid-distance from output shaft during $30000~hour$ at $30~^\circ C$ $500~N$ at $100~rpm$, force applied at mid-distance from output shaft during $10000~hour$ at $30~^\circ C$
Maximum axial force Fa	450 N at 100 rpm , during 30000 hour at 30°C 600 N at 100 rpm , during 10000 hour at 30°C
Moment of inertia	0.131 kg.cm²
Continuous output torque	44 N.m at 100 rpm at 30 °C
Maximum output torque	70 N.m at 100 rpm at 30 °C
Product weight	1.1 kg

Additional information

Environment

Noise level	58 dB at 1 m , no-load
IP degree of protection	IP54 at shaft output
Ambient temperature for operation	-2590 °C