Product data sheet Characteristics

GBX0800080852G

gearbox with straight teeth GBX - \varnothing 80 mm - reduction 8:1 - < 9 $^{\circ}$ - 50 N.m

Main

| Range compatibility | Lexium 05 |
|---------------------------|---------------------------------------|
| Product or component type | Planetary gearbox with straight teeth |
| Device short name | GBX |
| Product compatibility | BRH0852 |
| Casing diameter | 80 mm |
| Reduction ratio | 8:1 |
| Additional information | Lubricated for life |

Complementary

| Complementary | |
|--------------------------|---|
| Torsional backlash | < 9° |
| Torsional rigidity | 6 Nm/arcmin |
| Housing colour | Black |
| Housing material | Black anodized aluminium |
| Shaft material | C 45 |
| Service life in hours | 30000 h at 100 rpm at 30 °C |
| Mounting position | Any position |
| Efficiency | 96 % |
| Maximum radial force Fr | $650~N$ at $100~rpm$, force applied at mid-distance from output shaft during $30000~hour$ at $30~^\circ C$ $950~N$ at $100~rpm$, force applied at mid-distance from output shaft during $10000~hour$ at $30~^\circ C$ |
| Maximum axial force Fa | 900 N at 100 rpm , during 30000 hour at 30°C 1200 N at 100 rpm , during 10000 hour at 30°C |
| Moment of inertia | 0.39 kg.cm² |
| Continuous output torque | 50 N.m at 100 rpm at 30 °C |
| Maximum output torque | 80 N.m at 100 rpm at 30 °C |
| Product weight | 2.1 kg |
| | |

Environment

| Noise level | 60 dB at 1 m , no-load |
|-----------------------------------|------------------------|
| IP degree of protection | IP54 at shaft output |
| Ambient temperature for operation | -2590 °C |