Product data sheet Characteristics

GBX0800160853G

gearbox with straight teeth GBX - \varnothing 80 mm - reduction 16:1 - < 14 $^{\circ}$ - 120 N.m

Main

Range compatibility	Lexium 05
Product or component type	Planetary gearbox with straight teeth
Device short name	GBX
Product compatibility	BRH0853
Casing diameter	80 mm
Reduction ratio	16:1
Additional information	Lubricated for life

Complementary

oomplomontal y	
Torsional backlash	< 14 °
Torsional rigidity	6.5 Nm/arcmin
Housing colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Service life in hours	30000 h at 100 rpm at 30 °C
Mounting position	Any position
Efficiency	94 %
Maximum radial force Fr	$650~N$ at $100~rpm$, force applied at mid-distance from output shaft during $30000~hour$ at $30~^\circ C$ $950~N$ at $100~rpm$, force applied at mid-distance from output shaft during $10000~hour$ at $30~^\circ C$
Maximum axial force Fa	900 N at 100 rpm , during 30000 hour at 30°C 1200 N at 100 rpm , during 10000 hour at 30°C
Moment of inertia	0.5 kg.cm²
Continuous output torque	120 N.m at 100 rpm at 30 °C
Maximum output torque	192 N.m at 100 rpm at 30 °C
Product weight	2.6 kg

Environment

Noise level	60 dB at 1 m , no-load
IP degree of protection	IP54 at shaft output
Ambient temperature for operation	-2590 °C