

Main

Range compatibility	Lexium 05
Product or component type	Planetary gearbox with straight teeth
Device short name	GBX
Product compatibility	BRH0573
Casing diameter	80 mm
Reduction ratio	40:1
Additional information	Lubricated for life

Complementary

Torsional backlash	< 14 °
Torsional rigidity	6.5 Nm/arcmin
Housing colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Service life in hours	30000 h at 100 rpm at 30 °C
Mounting position	Any position
Efficiency	94 %
Maximum radial force Fr	650 N at 100 rpm , force applied at mid-distance from output shaft during 30000 hour at 30 °C 950 N at 100 rpm , force applied at mid-distance from output shaft during 10000 hour at 30 °C
Maximum axial force Fa	900 N at 100 rpm , during 30000 hour at 30 °C 1200 N at 100 rpm , during 10000 hour at 30 °C
Moment of inertia	0.39 kg.cm ²
Continuous output torque	110 N.m at 100 rpm at 30 °C
Maximum output torque	176 N.m at 100 rpm at 30 °C
Product weight	2.6 kg

Environment

Noise level	60 dB at 1 m , no-load
IP degree of protection	IP54 at shaft output
Ambient temperature for operation	-25...90 °C