Product data sheet Characteristics

GBX1200401001F

gearbox with straight teeth GBX - \emptyset 120 mm - reduction 40:1 - < 12 $^{\circ}$ - 230 N.m

Main	
Range compatibility	Lexium 05 Lexium 15
Product or component type	Planetary gearbox with straight teeth
Device short name	GBX
Product compatibility	BSH1001
Casing diameter	120 mm
Reduction ratio	40:1
Additional information	Lubricated for life

Complementary

Complementary	
Torsional backlash	< 12 °
Torsional rigidity	13 Nm/arcmin
Housing colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Service life in hours	30000 h at 100 rpm at 30 °C
Mounting position	Any position
Efficiency	94 %
Maximum radial force Fr	1500 N at 100 rpm , force applied at mid-distance from output shaft during 30000 hour at 30 $^{\circ}\text{C}$ 2000 N at 100 rpm , force applied at mid-distance from output shaft during 10000 hour at 30 $^{\circ}\text{C}$
Maximum axial force Fa	2100 N at 100 rpm , during 30000 hour at 30°C 2800 N at 100 rpm , during 10000 hour at 30°C
Moment of inertia	1.3 kg.cm²
Continuous output torque	230 N.m at 100 rpm at 30 °C
Maximum output torque	368 N.m at 100 rpm at 30 °C
Product weight	8 kg

Environment

Noise level	65 dB at 1 m , no-load
IP degree of protection	IP54 at shaft output
Ambient temperature for operation	-2590 °C