## Product data sheet Characteristics

## GBX1600031403F

gearbox with straight teeth GBX -  $\varnothing$  160 mm - reduction 3:1 - < 6  $^{\circ}$  - 400 N.m

Main	
Range compatibility	Lexium 05 Lexium 15
Product or component type	Planetary gearbox with straight teeth
Device short name	GBX
Product compatibility	BSH1403
Casing diameter	160 mm
Reduction ratio	3:1
Additional information	Lubricated for life

## Complementary

Complementary	
Torsional backlash	< 6 °
Torsional rigidity	38 Nm/arcmin
Housing colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Service life in hours	30000 h at 100 rpm at 30 °C
Mounting position	Any position
Efficiency	96 %
Maximum radial force Fr	4200 N at 100 rpm , force applied at mid-distance from output shaft during 30000 hour at 30 $^{\circ}\text{C}$ 6000 N at 100 rpm , force applied at mid-distance from output shaft during 10000 hour at 30 $^{\circ}\text{C}$
Maximum axial force Fa	6000 N at 100 rpm , during 30000 hour at 30°C 8000 N at 100 rpm , during 10000 hour at 30°C
Moment of inertia	12.14 kg.cm²
Continuous output torque	400 N.m at 100 rpm at 30 °C
Maximum output torque	640 N.m at 100 rpm at 30 °C
Product weight	18 kg

## Environment

Noise level	70 dB at 1 m , no-load
IP degree of protection	IP54 at shaft output
Ambient temperature for operation	-2590 °C