

PRODUCT-DETAILS

CA6-11E-F

CA6-11E-F Auxiliary Contact



General Information

Extended Product Type	CA6-11E-F
Product ID	GJL1201318R0002
EAN	4013614050992
Catalog Description	CA6-11E-F Auxiliary Contact
Long Description	CA6-11E-F is an auxiliary contact for side with 2 auxiliary contact and flat pin connection.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Popular Downloads

Data Sheet, Technical Information	1SBC100214C0201
Instructions and Manuals	2CDC102047M6801
Dimension Diagram	GJL1200444F0001

Dimensions

Product Net Width	20.3 mm
-------------------	---------

Product Net Height	48.5 mm
Product Net Depth / Length	46.5 mm
Product Net Weight	0.025 kg

Technical

Rated Operational Voltage	Auxiliary Circuit 690 V AC Auxiliary Circuit 250 V DC
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U_{imp})	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U_i)	690 V
Degree of Protection	IP20
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Number of Main Contacts NC	0
Number of Main Contacts NO	0
Conventional Free-air Thermal Current (I_{th})	Auxiliary Circuit 6 A
Product Name	Auxiliary Contact
Suitable For	B6-40-00-F BC6-40-00-F B7-40-00-F BC7-40-00-F
Suitable for Product Class	Mini Contactors

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Auxiliary Circuit 600 V AC/DC
Contact Rating UL/CSA	A600

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 5 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CB Certificate	1SAA938001-2001
CQC Certificate	CQC2003010304064035
cULus Certificate	cUL_E48139
cUR Certificate	1SAA938000-1901
Declaration of Conformity - CCC	2020980304001309
Declaration of Conformity - CE	1SAD938516-0001
EAC Certificate	1SAA938002-2701
GL Certificate	1SAA938000-0403
Instructions and Manuals	2CDC102047M6801
RMRS Certificate	1SAA938001-0703
RoHS Information	1SAD938516-0001
UL Certificate	UL_E48139
UR Certificate	1SAA938000-1801

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	142 mm
Package Level 1 Height	62 mm
Package Level 1 Gross Weight	0.315 kg
Package Level 1 EAN	4013614412141
Package Level 1 Units	10 piece

Classifications

Object Classification Code	K
ETIM 4	EC000041 - Auxiliary contact block
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522

Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors Accessories

