

PRODUCT-DETAILS

# CA6-11M-P

## CA6-11M-P Auxiliary Contact



### General Information

Extended Product Type	CA6-11M-P
Product ID	GJL1201319R0003
EAN	4013614051043
Catalog Description	CA6-11M-P Auxiliary Contact
Long Description	CA6-11M-P is an auxiliary contact for side with 2 auxiliary contact and soldering pins.

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

### Popular Downloads

Data Sheet, Technical Information	1SBC100214C0201
Instructions and Manuals	2CDC102047M6801
Dimension Diagram	GJL1200445F0001

### Dimensions

Product Net Width	20.3 mm
Product Net Height	48.5 mm

Product Net Depth / Length	51.5 mm
Product Net Weight	0.025 kg

## Technical

Rated Operational Voltage	Auxiliary Circuit 690 V AC Auxiliary Circuit 250 V DC
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U <sub>i</sub> )	690 V
Degree of Protection	IP20
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Number of Main Contacts NC	0
Number of Main Contacts NO	0
Conventional Free-air Thermal Current (I <sub>th</sub> )	Auxiliary Circuit 6 A
Product Name	Auxiliary Contact
Suitable For	B6-30-10-P BC6-30-10-P B7-30-10-P BC7-30-10-P
Suitable for Product Class	Mini Contactors

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	Auxiliary Circuit 600 V AC/DC
Contact Rating UL/CSA	A600

## Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 5 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU

## Certificates and Declarations (Document Number)

CB Certificate	1SAA938001-2001
----------------	-----------------

CQC Certificate	CQC2003010304064035
cULus Certificate	cUL_E48139
cUR Certificate	1SAA938000-1901
Declaration of Conformity - CCC	2020980304001309
Declaration of Conformity - CE	1SAD938516-0001
EAC Certificate	1SAA938002-2701
GL Certificate	1SAA938000-0403
Instructions and Manuals	2CDC102047M6801
RMRS Certificate	1SAA938001-0703
RoHS Information	1SAD938516-0001
UL Certificate	UL_E48139
UR Certificate	1SAA938000-1801

## Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	142 mm
Package Level 1 Height	62 mm
Package Level 1 Gross Weight	0.315 kg
Package Level 1 EAN	4013614412202
Package Level 1 Units	10 piece

## Classifications

Object Classification Code	K
ETIM 4	EC000041 - Auxiliary contact block
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors Accessories

