

PRODUCT-DETAILS

CA6-11N-P

CA6-11N-P Auxiliary Contact



General Information

Extended Product Type	CA6-11N-P
Product ID	GJL1201319R0004
EAN	4013614051050
Catalog Description	CA6-11N-P Auxiliary Contact
Long Description	CA6-11N-P is an auxiliary contact for side with 2 auxiliary contact and soldering pins.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Popular Downloads

Data Sheet, Technical Information	1SBC100214C0201
Instructions and Manuals	2CDC102047M6801
Dimension Diagram	GJL1200445F0001

Dimensions

Product Net Width	20.3 mm
Product Net Height	48.5 mm

Product Net Depth / Length	51.5 mm
Product Net Weight	0.025 kg

Technical

Rated Operational Voltage	Auxiliary Circuit 690 V AC Auxiliary Circuit 250 V DC
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U _{imp})	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U _i)	690 V
Degree of Protection	IP20
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Number of Main Contacts NC	0
Number of Main Contacts NO	0
Conventional Free-air Thermal Current (I _{th})	Auxiliary Circuit 6 A
Product Name	Auxiliary Contact
Suitable For	B6-30-01-P BC6-30-01-P B7-30-01-P BC7-30-01-P
Suitable for Product Class	Mini Contactors

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Auxiliary Circuit 600 V AC/DC
Contact Rating UL/CSA	A600

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 5 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CB Certificate	1SAA938001-2001
----------------	-----------------

CQC Certificate	CQC2003010304064035
cULus Certificate	cUL_E48139
cUR Certificate	1SAA938000-1901
Declaration of Conformity - CCC	2020980304001309
Declaration of Conformity - CE	1SAD938516-0001
EAC Certificate	1SAA938002-2701
GL Certificate	1SAA938000-0403
Instructions and Manuals	2CDC102047M6801
RMRS Certificate	1SAA938001-0703
RoHS Information	1SAD938516-0001
UL Certificate	UL_E48139
UR Certificate	1SAA938000-1801

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	142 mm
Package Level 1 Height	62 mm
Package Level 1 Gross Weight	0.315 kg
Package Level 1 EAN	4013614412219
Package Level 1 Units	10 piece

Classifications

Object Classification Code	K
ETIM 4	EC000041 - Auxiliary contact block
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522

Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors Accessories

