

Price* : 7.00 GBP



Main

Range of product	TeSys
Device short name	GS1AM
Product or component type	Auxiliary contact
Contact application	O, I and test position signalling
Contacts type and composition	1 NO
Contact operation	Early-break
[I _{th}] conventional free air thermal current	16 A (at 40 °C)
[I _e] rated operational current	3 A at 240 V AC-15 6 A at 120 V AC-15 1.5 A at 480 V AC-15 1.8 A at 400 V AC-15 2.8 A at 24 V DC-13 0.15 A at 400 V DC-13 0.27 A at 250 V DC-13 0.55 A at 125 V DC-13 1.4 A at 48 V DC-13

Complementary

Range compatibility	TeSys GS GS1 DD fuse-switch disconnectors
Mechanical durability	5000000 cycles
Electrical durability	1000000 cycles AC-15
Product compatibility	GS1
Switch rated current	50 A 100 A 250 A 32 A 60 A 125 A 600 A 315 A 630 A 200 A 1250 A 160 A 400 A 63 A

	800 A
Fuse type	DIN BS NFC
Type of operating handle	External left side External frontal External right side
Product weight	0.015 kg

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------