

Price* : 29.10 GBP



Main

| | |
|--|---|
| Range of product | TeSys |
| Device short name | GS1AN |
| Product or component type | Auxiliary contact |
| Contact application | O and I position signalling |
| Contacts type and composition | 1 NC + 1 NO |
| Contact operation | Instantaneous |
| [I _{th}] conventional free air thermal current | 20 A (at 40 °C) |
| [I _e] rated operational current | 1 A at 220 V DC-13 10 A at 230 V AC-15 12 A at 127 V AC-15 4 A at 48 V DC-13 6 A at 440 V AC-15 8 A at 400/415 V AC-15 1.2 A at 110 V DC-13 |

Complementary

| | |
|-----------------------|--|
| Mechanical durability | 30000 cycles |
| Electrical durability | 30000 cycles AC-15 |
| Product compatibility | GS |
| Switch rated current | 1250 A 160 A 400 A 50 A 63 A 800 A 250 A 315 A 600 A 125 A 100 A 60 A 200 A 630 A |
| Fuse type | NFC DIN BS |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|--------------------------|--|
| Type of operating handle | Direct frontal Direct right side External right side External frontal |
| Product weight | 0.132 kg |

Offer Sustainability

| | |
|----------------------------|--|
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|