

GS1AN11G

TeSys GS - auxiliary contact - 1 NC + 1 NO - left hand side - 50...1250 A



Main

Range of product	TeSys
Device short name	GS1AN
Product or component type	Auxiliary contact
Contact application	O and I position signalling
Contacts type and composition	1 NC + 1 NO
Contact operation	Instantaneous
[I _{th}] conventional free air thermal current	20 A (at 40 °C)
[I _e] rated operational current	1 A at 220 V DC-13 10 A at 230 V AC-15 12 A at 127 V AC-15 4 A at 48 V DC-13 6 A at 440 V AC-15 8 A at 400/415 V AC-15 1.2 A at 110 V DC-13

Complementary

Range compatibility	TeSys GS switch-disconnector-fuse
Mechanical durability	30000 cycles
Electrical durability	30000 cycles AC-15
Product compatibility	GS
Switch rated current	200 A 630 A 50 A 125 A 160 A 315 A 400 A 600 A 800 A 100 A 250 A 60 A 1250 A 63 A
Fuse type	BS NFC DIN

Type of operating handle	External left side
Product weight	0.131 kg

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------