

1000 piece

3 in 76 mm

3 in 76 mm

PRODUCT-DETAILS

GSC232

Package Level 1 Units Package Level 1 Width

Package Level 1 Height

2-PC OUTER SLV CONN ORG I.D. 0.232



General Information	
Extended Product Type	GSC232
Product ID	7TAI029060R0015
EAN	5414363114475
Catalog Description	2-PC OUTER SLV CONN ORG I.D. 0.232
Long Description	Two Piece Outer Sleeve Connector for Hexagonal Range, Length 1/4 Inch/6.4mm, Inner Diameter .232 Inches/5.90mm, Outer Diameter .263 Inches/6.70mm, Color Orange, Soft Bronze, Tin Plated
Ordering	
EAN	5414363114475
Dimensions	
Product Net Length	0, mm

Package Level 1 Depth / Length	3.5 in 89 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	6.9 in 175 mm
Package Level 2 Height	4.5 in 114 mm
Package Level 2 Depth / Length	16.1 in 409 mm

Additional Information	
Brand / Label	Sta-Kon
Color	Orange
Effective Date	19680516
Material	Soft Bronze
Number of Batteries	0
Product Name	TERMINALS,ELECTRICAL SPLICES
Product Type	Two-Piece Outer Sleeve Connector
Special Functions	Shielded cable grounding system made of 2 cylindrical sleeves (inner sleeve + outer sleeve), for solderless crimp connection. Outer sleeve for the Hexagonal Range (the outer sleeve is crimped with a hand tool and the result is a hexagonal-shaped crimp), for grounding shielded and coaxial cables. The sleeves are color coded according to their size. Millions of installations in communications, aerospace, electronic, telephone, radio and TV applications.
UPC	786210813905

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	GSC232	
Instructions and Manuals	GSC232	

Classifications		
ETIM 6	EC002650 - Connection for screened wires	
ETIM 7	EC002650 - Connection for screened wires	
UNSPSC	39121432	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4603 >> Electrical terminals	

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Compression\ \&\ Mechanical\ Connectors$

GSC232 3

